

In the Specification:

Please delete paragraph [0041] and replace with the following new paragraph [0041].

[0041] ~~[[Fig. 4 is a]]~~ **Figs. 4-1 and 4-2 are** flow ~~[[chart]]~~ charts showing an embodiment of discriminating LA and RA driven atrial flutter;

Please delete paragraph [0041] and replace with the following new paragraph [0042].

[0042] **Fig. 5** is a more detailed embodiment of one of the determinations of the embodiment illustrated in ~~[[Fig. 4]]~~ **Figs. 4-1 and 4-2;**

Please delete paragraph [0079] and replace with the following new paragraph [0079].

[0079] If the device 10 determines in state 214 that the atrial rates are not stable, the device 10 concludes that the rhythm is classified as atrial fibrillation and appropriate defibrillation shocking therapy would then be delivered ~~as previously described in state 216.~~

Please delete paragraph [0090] and replace with the following new paragraph [0090].

[0090] **Fig. 8** illustrates a sample waveform of an electrocardiogram (ECG) of cardiac and stimulation therapy provided in accordance with embodiments of the invention and as observed at the surface of a patient's body via a plurality of surface electrodes. ~~In this embodiment, the observed signals are shown with respect to the lead II configuration.~~ The initial portion of the waveform illustrates an atrial flutter condition. In this example, a determination is made that the flutter originated in the right atrium in accordance with the aspects of the invention previously described.